

PREMIER SERIES

9,000 BTU

BZ33-CASS09-P



FEATURES

- Premier Series
- Single & multi-zone compatible
- 360° air flow
- Electrical box within unit
- Auto defrost
- 24-hour timer
- Auto restart function
- Golden Fin anti-corrosive coating
- Built-in drain pump
- Independent vane control
- Wireless handheld remote control included
- Front grill sold separately
- Compatible with BZ33-WCON1 and BZ33-WCON2

SINGLE & MULTI-ZONE

The unit is compatible for either single or multiple zone applications.

FOLLOW ME MODE

Senses indoor temperature at handheld remote or Breeze33 wired controller, rather than at the indoor equipment.

GOLDEN FIN COATING

Prevents corrosive build-up and improves efficiency while protecting the condenser from harsh weather and elements.

AUTO DEFROST

In low temperatures, the auto defrost feature will keep the evaporator from freezing.

AUTO RESTART

In the event of a power failure, the unit will remember and restart the previous settings when power returns.

24-HOUR TIMER

Preset the unit to automatically turn on or off.



*5 year warranty on parts. 7 year warranty on compressor.

PREMIER SERIES

| UNIT | ID NO. | MODEL | INDOOR FAN MOTOR | | |
|----------------------------|----------|-------------------------|-----------------------------|---------|---------------------------|
| Indoor | .3473427 | BZ33-CASS09-P | Input | W | 45 |
| Grill [†] | .3473437 | BZ33-GRILL1-P | RLA | А | 0.90 |
| | | | Speed (High/Med/Low) | r/min | 600 / 520 / 460 |
| PERFORMANCE | | | Air Flow (High/Med/Low) | CFM | 353 / 306 / 271 |
| Nominal Cooling (Capacity) | BTU/H | 9,000 (3,250 - 9,500) | Noise Level (High/Med/Low) | dBA | 41 / 39 / 37 |
| Nominal Heating (Capacity) | BTU/H | 10,000 (3,050 - 10,500) | | | |
| SEER | BTU/W | 19.5 | INDOOR UNIT DIMENSIONS | | |
| EER | BTU/W | 13.0 | Product Body (W x D x H) | In | 22-1/5 x 22-1/5 x 10-1/4 |
| HSPF4 | BTU/W | 10.0 | Product Grill (W x D x H) | In | 25-1/2 x 25-1/2 x 2 |
| HSPF5 | BTU/W | 8.1 | Packaging Body (W x D x H) | In | 25-4/5 x 25-4/5 x 11-2/5 |
| | | | Packaging Grill (W x D x H) | In | 28-1/10 x 28-1/10 x 4-4/5 |
| REFRIGERANT PIPING | | | Net/Gross Body Weight | Lbs | 35.27 / 41.88 |
| Liquid | In | 1/4 | Net/Gross Grill Weight | Lbs | 5.51 / 9.92 |
| Gas | In | 3/8 | | | |
| | | | ELECTRICAL DATA | | |
| ROOM TEMPERATURE | | | Min. Circuit Ampacity | Α | 1.2 |
| Cooling/Heating | °F | 62~90 / 32~86 | Max. Fuse | Α | 15 |
| | | | Design Pressure | PSIG | 550 / 340 |
| SPECIFICATIONS | | | Power Supply | Ph/V/Hz | 1 / 208/230 / 60 |
| Controller | | Wireless Remote | | | |
| Warranty | | Yes* | | | |

†Sold separately.



