

PREMIER SERIES**24,000 BTU****BZ33-CASS24-P****FEATURES**

- Premier Series
- 360° air flow
- Electrical box within unit
- Auto defrost
- 24-hour timer
- Auto restart function
- Golden Fin anti-corrosive coating
- Built-in drain pump
- Independent vane control
- Wireless handheld remote control included
- Front grill sold separately
- Compatible with BZ33-WCON1 and BZ33-WCON2

MULTI-ZONE

The unit is compatible for multiple zone applications.

FOLLOW ME MODE

Senses indoor temperature at handheld remote or Breeze33 wired controller, rather than at the indoor equipment.

GOLDEN FIN COATING

Prevents corrosive build-up and improves efficiency while protecting the condenser from harsh weather and elements.

AUTO DEFROST

In low temperatures, the auto defrost feature will keep the evaporator from freezing.

AUTO RESTART

In the event of a power failure, the unit will remember and restart the previous settings when power returns.

24-HOUR TIMER

Preset the unit to automatically turn on or off.



CASSETTE

PREMIER SERIES

UNIT	ID NO.	MODEL
Indoor	.3473434	BZ33-CASS24-P
Grill†	.3473438	BZ33-GRILL2-P

PERFORMANCE

Nominal Cooling (Capacity)	BTU/H	24,000 (7,300 - 24,200)
Nominal Heating (Capacity)	BTU/H	24,000 (7,100 - 29,000)
SEER	BTU/W	19.0
EER	BTU/W	11.0
HSPF4	BTU/W	10.5
HSPF5	BTU/W	9.0

REFRIGERANT PIPING

Liquid	In	3/8
Gas	In	5/8

ROOM TEMPERATURE

Cooling/Heating	°F	62~90 / 32~86
-----------------	----	---------------

SPECIFICATIONS

Controller	Wireless Remote
Warranty	Yes*

*5 year warranty on parts. 7 year warranty on compressor.

†Sold separately.

INDOOR FAN MOTOR

Input	W	42
RLA	A	2.00
Speed (High/Med/Low)	r/min	600 / 520 / 450
Air Flow (High/Med/Low)	CFM	820 / 740 / 590
Noise Level (High/Med/Low)	dBA	51 / 47 / 43

INDOOR UNIT DIMENSIONS

Product Body (W x D x H)	In	33 x 33 x 8
Product Grill (W x D x H)	In	37-2/5 x 37-2/5 x 2-1/10
Packaging Body (W x D x H)	In	35-2/5 x 35-2/5 x 8-9/10
Packaging Grill (W x D x H)	In	40-3/4 x 40-3/4 x 3-1/2
Net/Gross Body Weight	Lbs	45.19 / 52.91
Net/Gross Grill Weight	Lbs	11.02 / 17.64

ELECTRICAL DATA

Min. Circuit Ampacity	A	1.30
Max. Fuse	A	17.50
Design Pressure	PSIG	550 / 340
Power Supply	Ph/V/Hz	1 / 208/230 / 60

