

PREMIER SERIES

18,000 BTU

BZ33-HP182Z2-P



FEATURES

- Premier Series
- Two zone compatibility
- Space-saving installation
- Crank case & basepan heater included

COMPATIBLE UNITS



CONSOLE

BZ33ICM12-P



WALL MOUNT

BZ33-HYP09WALL2-P

BZ33-HYP12WALL2-P



DUCTED SYSTEM

BZ33-DIDU9-P

BZ33-DIDU12-P



CASSETTE

BZ33-CASS09-P

BZ33-CASS12-P

MULTI-ZONE

The unit is compatible for a multiple zone application. Must be used with two zones.

SPACE-SAVING INSTALLATION

Save space with the ability to connect up to 2 indoor units. Uses up to 50% less space than traditional outdoor units.

PREMIER SERIES

UNIT	ID NO.	MODEL
Outdoor	.3473414	BZ33-HP182Z2-P

COOLING

Capacity	BTU/H	18,000
EER	BTU/W	12.5
SEER	BTU/W	22.5

HEATING

Capacity (at 47°F)	BTU/H	19,000
COP (at 47°F)	W	3.6
HSPF4 (at 47°F)	BTU/W	10.3
HSPF5 (at 47°F)	BTU/W	8.8
Capacity (at 17°F)	BTU/H	12,000
Capacity (at 5°F)	BTU/H	13,900

COMPRESSOR

Type	Rotary	
Capacity	W	15,388
Input	W	1,170
Rated Current (RLA)	A	10
Refrigerant Oil/Charge	mL	Ester Oil VG74 / 500

REFRIGERANT PIPING

Liquid	In	2 x 1/4
Gas	In	2 x 3/8
Max. Length (All Rooms)	Ft	131
Max. Length (1 Indoor Unit)	Ft	82
Max. Height Difference (Between Indoor/Outdoor)	Ft	49
Max. Height Difference (Between Indoor Units)	Ft	33

AMBIENT TEMPERATURE

Cooling	°F	-13~122
Heating	°F	-13~86

SPECIFICATIONS

Refrigerant Type	R410A
Warranty	Yes*

OUTDOOR FAN MOTOR

Input	W	115
RLA	A	0.74
Speed	r/min	150 / 200 / 250 / 300 / 350 / 450 550 / 650 / 800 / 850
Air Flow	CFM	1,390
Noise Level	dBA	62.40

OUTDOOR UNIT DIMENSIONS

Product (W x D x H)	In	33-1/4 x 14-3/10 x 27-3/5
Packaging (W x D x H)	In	38 x 15-1/2 x 29-7/10
Net/Gross Weight	Lbs	105.82 / 114.64

ELECTRICAL DATA

Min. Circuit Ampacity	A	18
Max. Fuse	A	25
Refrigerant Precharge	Ft	25
Additional Charge/Ft	Oz	0.161
Design Pressure	PSIG	550 / 340
Power Supply	Ph/V/Hz	1 / 208/230 / 60

*5 year warranty on parts. 7 year warranty on compressor.