

PREMIER SERIES

28,000 BTU

BZ33-HP273Z2-P



FEATURES

- Premier Series
- 2-3 zone compatibility
- Space-saving installation
- Crank case & basepan heater included

COMPATIBLE UNITS



CONSOLE

BZ33ICM12-P



WALL MOUNT

BZ33-HYP09WALL2-P

BZ33-HYP12WALL2-P

BZ33-HYP18WALL2-P



DUCTED SYSTEM

BZ33-DIDU9-P

BZ33-DIDU12-P

BZ33-DIDU18-P



CASSETTE

BZ33-CASS09-P

BZ33-CASS12-P

BZ33-CASS18-P



CEILING & FLOOR SYSTEM

BZ33-IFMU18-P

MULTI-ZONE

The unit is compatible for multiple zone applications, up to three zones. Must start installation with two zones.

SPACE-SAVING INSTALLATION

Save space with the ability to connect up to 3 indoor units. Uses up to 50% less space than traditional outdoor units.

PREMIER SERIES

UNIT	ID NO.	MODEL
Outdoor	.3473415	BZ33-HP273Z2-P

COOLING

Capacity	BTU/H	28,000
EER	BTU/W	12.5
SEER	BTU/W	23

HEATING

Capacity (at 47°F)	BTU/H	28,000
COP (at 47°F)	W	3.9
HSPF4 (at 47°F)	BTU/W	10.3
HSPF5 (at 47°F)	BTU/W	8.5
Capacity (at 17°F)	BTU/H	17,200
Capacity (at 5°F)	BTU/H	21,900

COMPRESSOR

Type	Rotary	
Capacity	W	24,345
Input	W	1,970
Rated Current (RLA)	A	20
Refrigerant Oil/Charge	mL	Ester Oil VG74 / 670

REFRIGERANT PIPING

Liquid	In	3 x 1/4
Gas	In	3 x 3/8
Max. Length (All Rooms)	Ft	197
Max. Length (1 Indoor Unit)	Ft	98
Max. Height Difference (Between Indoor/Outdoor)	Ft	49
Max. Height Difference (Between Indoor Units)	Ft	33

AMBIENT TEMPERATURE

Cooling	°F	-13~122
Heating	°F	-13~86

SPECIFICATIONS

Refrigerant Type	R410A
Warranty	Yes*

OUTDOOR FAN MOTOR

Input	W	150
RLA	A	0.90
Speed	r/min	150 / 200 / 250 / 300 / 400 / 500 600 / 750 / 900 / 1,000
Air Flow	CFM	2,130
Noise Level	dBA	63.40

OUTDOOR UNIT DIMENSIONS

Product (W x D x H)	In	37-1/4 x 16-1/10 x 31-9/10
Packaging (W x D x H)	In	42-9/10 x 19-7/10 x 34-1/2
Net/Gross Weight	Lbs	149.91 / 160.94

ELECTRICAL DATA

Min. Circuit Ampacity	A	25
Max. Fuse	A	35
Refrigerant Precharge	Ft	25
Additional Charge/Ft	Oz	0.161
Design Pressure	PSIG	550 / 340
Power Supply	Ph/V/Hz	1 / 208/230 / 60

*5 year warranty on parts. 7 year warranty on compressor.