# **PREMIER SERIES**

36,000 BTU

#### BZ33-HP364Z2-P



## **FEATURES**

- Premier Series
- 2-4 zone compatibility
- Space-saving installation
- Crank case & basepan heater included

#### **COMPATIBLE UNITS**











CONSOLE	WALL MOUNT	<b>DUCTED SYSTEM</b>	CASSETTE	<b>CEILING &amp; FLOOR SYSTEM</b>
BZ33ICM12-P	BZ33-HYP09WALL2-P	BZ33-DIDU9-P	BZ33-CASS09-P	BZ33-IFMU18-P
	BZ33-HYP12WALL2-P	BZ33-DIDU12-P	BZ33-CASS12-P	
	BZ33-HYP18WALL2-P	BZ33-DIDU18-P	BZ33-CASS18-P	
	BZ33-HYP24WALL2-P		BZ33-CASS24-P	

### **MULTI-ZONE**

The unit is compatible for multiple zone applications, up to four zones. Must start installation with at least two zones.

## **SPACE-SAVING INSTALLATION**

Save space with the ability to connect up to 4 indoor units. Uses up to 50% less space than traditional outdoor units.



## **PREMIER SERIES**

UNIT	ID NO.	MODEL	AMBIENT TEMPERATURE	
Outdoor	.3473416	BZ33-HP364Z2-P	Cooling	°F
COOLING			Heating	°F
Capacity	BTU/H	36,000	SPECIFICATIONS	
EER	BTU/W	11.5	Refrigerant Type	
SEER	BTU/W	22.5	Warranty	
HEATING			OUTDOOR FAN MOTOR	
Capacity (at 47°F)	BTU/H	36,000	Input	W
COP (at 47°F)	W	3.4	RLA	Α
HSPF4 (at 47°F)	BTU/W	10.2	Speed	r/m
HSPF5 (at 47°F)	BTU/W	8.7	Speed	1/111
Capacity (at 17°F)	BTU/H	23,000	Air Flow	CF
Capacity (at 5°F)	BTU/H	28,000	Noise Level	dB
COMPRESSOR			OUTDOOR UNIT DIMENSION	NS
Туре		Rotary	Product (W x D x H)	In
Capacity	W	32,380	Packaging (W x D x H)	Ir
Input	W	2,600	Net/Gross Weight	Lb
Rated Current (RLA)	А	22		
Refrigerant Oil/Charge	mL	Ester Oil VG74 / 1,000	ELECTRICAL DATA	
			Min. Circuit Ampacity	А
REFRIGERANT PIPING			Max. Fuse	Α
Liquid	In	4 x 1/4	Refrigerant Precharge	Ft
Gas	In	3 x 3/8 + 1 x 1/2	Additional Charge/Ft	O
Max. Length (All Rooms)	Ft	262	Design Pressure	PSI
Max. Length (1 Indoor Unit)	Ft	115	Power Supply	Ph/V
Max. Height Difference (Between Indoor/Outdoor)	Ft	49	*5 year warranty on parts. 7 year warranty	on compress
Max. Height Difference (Between Indoor Units)	Ft	33		

ΔMR	IFNT	TEM	IPFR	ATURE	

Cooling	°F	-13~122
Heating	°F	-13~86

Refrigerant Type	R410A
Warranty	Yes*

Input	W	150
RLA	Α	1.3
Speed	r/min	150 / 200 / 250 / 300 / 400 / 500 600 / 750 / 900 / 1,000
Air Flow	CFM	2,130
Noise Level	dBA	62.3

Product (W x D x H)	In	37-1/4 x 16-1/10 x 31-9/10
Packaging (W x D x H)	In	42-9/10 x 19-7/10 x 34-1/2
Net/Gross Weight	Lbs	156.53 / 167.55

Min. Circuit Ampacity	А	30	
Max. Fuse	Α	45	
Refrigerant Precharge	Ft	25	
Additional Charge/Ft	Oz	0.161	
Design Pressure	PSIG	550 / 340	
Power Supply	Ph/V/Hz	1 / 208/230 / 60	



