

BZ33-HYP18HP2Z2



**FEATURES**

- Up to 2-zone compatibility
- Space-saving installation

**COMPATIBLE UNITS**



**CONSOLE**

BZ33ICM12



**WALL MOUNT**

BZ33-HYP09WALL2  
BZ33-HYP12WALL2  
BZ33-HYP18WALL2



**DUCTED SYSTEM**

BZ33-DIDU9  
BZ33-DIDU12



**CASSETTE**

BZ33-CASS09  
BZ33-CASS12

**MULTI-ZONE**

The unit is compatible for multiple zone applications, up to 2 zones.

**SPACE-SAVING INSTALLATION**

Save space with the ability to connect up to 2 indoor units. Uses up to 50% less space than traditional outdoor units.

**AMBIENT HEATING & COOLING**

Low ambient heating down to -22°F. Ambient cooling as low as -22°F and as high as 122°F.

**19,000 BTU**

UNIT	ID NO.	MODEL
Outdoor	.3481265	BZ33-HYP18HP2Z2

### COOLING

Capacity	BTU/H	19,000
EER	BTU/W	12.5
SEER	BTU/W	21.5

### HEATING

Capacity	BTU/H	20,000
Input	W	1,724
Current	A	7.5
COP	W/W	3.4
HSPF4	BTU/W	9.8
HSPF5	BTU/W	8.5

### COMPRESSOR

Type	Rotary	
Capacity	W	24,345
Input	W	1,970
Rated Current (RLA)	A	20
Refrigerant Oil/Charge	mL	Ester Oil VG74 / 670

### REFRIGERANT PIPING

Liquid	In	2 x 1/4
Gas	In	2 x 3/8
Max. Length (All Rooms)	Ft	131
Max. Length (1 Indoor Unit)	Ft	82
Max. Height Difference (Between Indoor/Outdoor)	Ft	49
Max. Height Difference (Between Indoor Units)	Ft	33

### AMBIENT TEMPERATURE

Cooling	°F	-22~122
Heating	°F	-22~86

### SPECIFICATIONS

Refrigerant Type	R410A
Warranty	Yes*

### OUTDOOR FAN MOTOR

Input	W	150
RLA	A	1.39
Speed	r/min	900 / 750 / 600
Air Flow	CFM	2,129
Noise Level	dBA	63.4

### OUTDOOR UNIT DIMENSIONS

Product (W x D x H)	In	37-1/4 x 14 x 31-9/10
Packaging (W x D x H)	In	42-9/10 x 19-7/10 x 34
Net/Gross Weight	Lbs	149.91 / 160.94

### ELECTRICAL DATA

Min. Circuit Ampacity	A	25
Max. Fuse	A	35
Refrigerant Precharge	Ft	49
Additional Charge/Ft	Oz	0.161
Design Pressure	PSIG	550 / 340
Power Supply	Ph/V/Hz	1 / 208/230 / 60

\*5 year warranty on parts. 7 year warranty on compressor.

