PREMIER SERIES

28,000 BTU

BZ33-HYP27HP3Z2-P



FEATURES

- Premier Series
- 2-3 zone compatibility
- Space-saving installation
- Crank case & basepan heater included

COMPATIBLE UNITS











CONSOLE	WALL MOUNT	DUCTED SYSTEM	CASSETTE	CEILING & FLOOR SYSTEM
BZ33ICM12-P	BZ33-HYP09WALL2-P	BZ33-DIDU9-P	BZ33-CASS09-P	BZ33-IFMU18-P
	BZ33-HYP12WALL2-P	BZ33-DIDU12-P	BZ33-CASS12-P	
	R733-HYP18WALL2-P	R733-DIDLI18-P	B733-CASS18-P	

MULTI-ZONE

The unit is compatible for multiple zone applications, up to three zones. Must start installation with two zones.

SPACE-SAVING INSTALLATION

Save space with the ability to connect up to 3 indoor units. Uses up to 50% less space than traditional outdoor units.

AMBIENT HEATING & COOLING

Low ambient heating down to -22°F. Ambient cooling as low as -22°F and as high as 122°F.



PREMIER SERIES

UNIT	ID NO.	MODEL
Outdoor	.3481263	BZ33-HYP27HP3Z2-P
COOLING		
Capacity	BTU/H	28,000
EER	BTU/W	13
SEER	BTU/W	22
HEATING		
Capacity	BTU/H	28,000
Input	W	2,345
Current	Α	10.2
COP	W/W	3.5
HSPF4	BTU/W	10.4
HSPF5	BTU/W	9
COMPRESSOR		
Туре		Rotary
Capacity	W	32,380
Input	W	2,600
Rated Current (RLA)	Α	22
Refrigerant Oil/Charge	mL	Ester Oil VG74 / 1000
REFRIGERANT PIPING		
Liquid	In	3 x 1/4
Gas	In	3 x 3/8
Max. Length (All Rooms)	Ft	197
Max. Length (1 Indoor Unit)	Ft	98
Max. Height Difference (Between Indoor/Outdoor)	Ft	49
Max. Height Difference (Between Indoor Units)	Ft	33

Cooling	°F	-22~122	
Heating	°F	-22~86	
SPECIFICATIONS			
Refrigerant Type		R410A	
Warranty		Yes*	
OUTDOOR FAN MOTOR			
Input	W	150	
RLA	Α	1.39	
Speed	r/min	900 / 750 / 600	
Air Flow	CFM	2,147	
Noise Level	dBA	62.3	
OUTDOOR UNIT DIMENSION	ONS		
Product (W x D x H)	In	37-1/4 x 16-1/10 x 31-9/10	
Packaging (W x D x H)	In	42-9/10 x 19-7/10 x 34	
Net/Gross Weight	Lbs	156.53 / 167.55	
ELECTRICAL DATA			
Min. Circuit Ampacity	А	30	
Max. Fuse	А	45	
Refrigerant Precharge	Ft	74	
Additional Charge/Ft	Oz	0.161	
Design Pressure	PSIG	550 / 340	
Design Pressure			



