

PREMIER SERIES

48,000 BTU

BZ33-HYP48HP5Z2-P



FEATURES

- Premier Series
- 2-5 zone compatibility
- Space-saving installation
- Crank case & basepan heater included

COMPATIBLE UNITS



CONSOLE

BZ33ICM12-P



WALL MOUNT

BZ33-HYP09WALL2-P
BZ33-HYP12WALL2-P
BZ33-HYP18WALL2-P
BZ33-HYP24WALL2-P



DUCTED SYSTEM

BZ33-DIDU9-P
BZ33-DIDU12-P
BZ33-DIDU18-P



CASSETTE

BZ33-CASS09-P
BZ33-CASS12-P
BZ33-CASS18-P
BZ33-CASS24-P



CEILING & FLOOR SYSTEM

BZ33-IFMU18-P

MULTI-ZONE

The unit is compatible for multiple zone applications, up to five zones. Must start installation with at least two zones.

SPACE-SAVING INSTALLATION

Save space with the ability to connect up to 5 indoor units. Uses up to 50% less space than traditional outdoor units.

AMBIENT HEATING & COOLING

Low ambient heating down to -22°F. Ambient cooling as low as -22°F and as high as 122°F.



OUTDOOR HYPER PRO MULTI-ZONE UNIT

PREMIER SERIES

UNIT	ID NO.	MODEL
Outdoor	.3494048	BZ33-HYP48HP5Z2-P

COOLING

Capacity	BTU/H	48,000
EER	BTU/W	11.6
SEER	BTU/W	21.5

HEATING

Capacity	BTU/H	49,000
COP	W	3.59
HSPF4	BTU/W	10.3
HSPF5	BTU/W	8.6
Capacity (at 5°F)	BTU/H	48,000
Capacity (at -4°F)	BTU/H	42,000

COMPRESSOR

Type		Rotary
Capacity	W	44,015
Input	W	3,565
Rated Current (RLA)	A	22.21
Refrigerant Oil/Charge	mL	Ester Oil VG74 / 1,460

REFRIGERANT PIPING

Liquid	In	5 x 1/4
Gas	In	3 x 3/8 + 2 x 1/2
Max. Length (All Rooms)	Ft	262
Max. Length (1 Indoor Unit)	Ft	115
Max. Height Difference (Between Indoor/Outdoor)	Ft	49
Max. Height Difference (Between Indoor Units)	Ft	33

AMBIENT TEMPERATURE

Cooling	°F	-22~122
Heating	°F	-22~86

SPECIFICATIONS

Refrigerant Type	R410A
Warranty	Yes*

OUTDOOR FAN MOTOR

Input	W	126
RLA	A	1.0
Speed	r/min	800 / 700 / 600
Air Flow	CFM	4,500
Noise Level	dBA	64

OUTDOOR UNIT DIMENSIONS

Product (W x D x H)	In	37-1/2 x 16-3/10 x 52-1/2
Packaging (W x D x H)	In	43 x 19-1/2 x 58-1/4
Net/Gross Weight	Lbs	238.32 / 269.84

ELECTRICAL DATA

Min. Circuit Ampacity	A	35
Max. Fuse	A	50
Refrigerant Precharge	Ft	125
Additional Charge/Ft	Oz	0.161 or 0.322
Design Pressure	PSIG	550 / 340
Power Supply	Ph/V/Hz	1 / 208/230 / 60

*5 year warranty on parts. 7 year warranty on compressor.

