

**COMFORT SERIES****9,000 BTU****BZ33-HP09WALL1-C****BZ33-HP09OUT1-C****FEATURES**

- Comfort Series
- Two-way draining
- Golden Fin anti-corrosive coating
- Auto restart function
- Crank case & base pan heater included
- Auto defrost
- 24-hour timer
- Wireless remote control included
- 115V, single phase

**TWO-WAY DRAINING**

Piping, drainage, and connections are able to be installed on the right and left sides.

**FOLLOW ME MODE**

Senses indoor temperature at handheld remote or Breeze33 wired controller, rather than at the indoor equipment.

**GOLDEN FIN COATING**

Prevents corrosive build-up and improves efficiency while protecting the condenser from harsh weather and elements.

**AUTO DEFROST**

In low temperatures, the auto defrost feature will keep the evaporator from freezing.

**AUTO RESTART**

In the event of a power failure, the unit will remember and restart the previous settings when power returns.

**24-HOUR TIMER**

Preset the unit to automatically turn on or off.

UNIT			COMFORT SERIES		
ID NO.	MODEL		INDOOR FAN MOTOR		
Indoor	.3473331	BZ33-HP09WALL1-C	Input	W	35.20
Outdoor	.3473335	BZ33-HP09OUT1-C	Output	W	20
			RLA	A	0.71
			Speed (High/Med/Low)	r/min	1,050 / 850 / 600
			Air Flow (High/Med/Low)	CFM	247 / 182 / 129
			Noise Level (High/Med/Low)	dBA	38 / 32 / 25
COOLING			INDOOR UNIT DIMENSIONS		
Capacity (Range)	BTU/H	9,000 (3,600 - 10,300)	Product (W x D x H)	In	28-2/5 x 7-2/5 x 11-2/5
Input	W	782	Packaging (W x D x H)	In	31-1/10 x 10-3/5 x 14-1/2
Rated Current	A	6.8	Net/Gross Weight	Lbs	17.2 / 22.7
EER	BTU/W	11.5			
SEER	BTU/W	19			
HEATING			OUTDOOR FAN MOTOR		
Capacity (Range)	BTU/H	10,000 (3,500 - 10,900)	Input	W	58
Input	W	925	Output	W	34
Rated Current	A	8.1	RLA	A	0.39
COP	W/W	3.11	Speed	r/min	800 / 750 / 650
HSPF4	BTU/W	10	Air Flow	CFM	1,176.47
HSPF5	BTU/W	7.8	Noise Level	dBA	52
COMPRESSOR			OUTDOOR UNIT DIMENSIONS		
Type		Rotary	Product (W x D x H)	In	30-3/10 x 11-4/5 x 21-4/5
Capacity	W	3,100	Packaging (W x D x H)	In	35-2/5 x 13-1/2 x 23
Input	W	790	Net/Gross Weight	Lbs	66.8 / 71.87
Rated Current (RLA)	A	6			
Refrigerant Oil/Charge	mL	Ester Oil VG74 / 310			
REFRIGERANT PIPING			ELECTRICAL DATA		
Liquid	In	1/4	Min. Circuit Ampacity	A	16
Gas	In	3/8	Max. Fuse	A	20
Max. Refrigerant Pipe Length	Ft	82	Refrigerant Precharge	Ft	25
Max. Different in Level	Ft	33	Additional Charge/Ft	Oz	0.161
ROOM TEMPERATURE			Design Pressure	PSIG	550 / 340
Indoor (Cooling/Heating)	°F	62~90 / 32~86	Connection Wiring		16AWG*4, Stranded, Unshielded
Outdoor (Cooling/Heating)	°F	5~122 / 5~86	Power Supply	Ph/V/Hz	1 / 115 / 60
SPECIFICATIONS			RECOMMENDED ACCESSORIES		
Refrigerant Type		R410A	BZ33-WCON1		.3496301
Thermostat Type		Wireless Remote	Description		Wired Controller
Warranty		Yes*	Compatible with		All Breeze33 Indoor Mini Split Equipment

\*5 year warranty on parts, 7 year warranty on compressor.