

**COMFORT SERIES****18,000 BTU****BZ33-HP18WALL2-C****BZ33-HP18OUT2-C****FEATURES**

- Two-way draining
- Golden Fin anti-corrosive coating
- Auto restart function
- Crank case & base pan heater included
- Auto defrost
- 24-hour timer
- Wireless remote control included
- 208/230V, single phase

**TWO-WAY DRAINING**

Piping, drainage, and connections are able to be installed on the right and left sides.

**FOLLOW ME MODE**

Senses indoor temperature at handheld remote or Breeze33 wired controller, rather than at the indoor equipment.

**GOLDEN FIN COATING**

Prevents corrosive build-up and improves efficiency while protecting the condenser from harsh weather and elements.

**AUTO DEFROST**

In low temperatures, the auto defrost feature will keep the evaporator from freezing.

**AUTO RESTART**

In the event of a power failure, the unit will remember and restart the previous settings when power returns.

**24-HOUR TIMER**

Preset the unit to automatically turn on or off.

UNIT			COMFORT SERIES		
ID NO.	MODEL		INDOOR FAN MOTOR		
Indoor	.3473404	BZ33-HP18WALL2-C	Input	W	36
Outdoor	.3473405	BZ33-HP18OUT2-C	Output	W	30
COOLING			RLA	A	0.11
Capacity (Range)	BTU/H	18,000 (4,500 - 18,500)	Speed (High/Med/Low)	r/min	1,100 / 800 / 750
Input	W	1,645	Air Flow (High/Med/Low)	CFM	449 / 393 / 262
Rated Current	A	7.35	Noise Level (High/Med/Low)	dBA	43 / 35 / 30.5
EER	BTU/W	11.0	INDOOR UNIT DIMENSIONS		
SEER	BTU/W	19	Product (W x D x H)	In	38 x 8-1/2 x 12-1/2
HEATING			Packaging (W x D x H)	In	41-1/10 x 12 x 16
Capacity (Range)	BTU/H	18,000 (4,600 - 19,000)	Net/Gross Weight	Lbs	24 / 32.19
Input	W	1,700	OUTDOOR FAN MOTOR		
Rated Current	A	7.4	Input	W	58
COP	W/W	3.1	Output	W	34
HSPF4	BTU/W	10.0	RLA	A	0.39
HSPF5	BTU/W	8.0	Speed	r/min	800 / 750 / 650
COMPRESSOR			Air Flow	CFM	1,176
Type	Rotary		Noise Level	dBA	57.5
Capacity	W	4,370	OUTDOOR UNIT DIMENSIONS		
Input	W	1,135	Product (W x D x H)	In	31-1/2 x 13-1/10 x 21-4/5
Rated Current (RLA)	A	7.5	Packaging (W x D x H)	In	36-1/5 x 15-2/5 x 24-1/5
Refrigerant Oil/Charge	mL	Ester Oil VG74 / 440	Net/Gross Weight	Lbs	79.8 / 85.76
REFRIGERANT PIPING			ELECTRICAL DATA		
Liquid	In	1/4	Min. Circuit Ampacity	A	15
Gas	In	1/2	Max. Fuse	A	20
Max. Refrigerant Pipe Length	Ft	98	Refrigerant Precharge	Ft	25
Max. Different in Level	Ft	66	Additional Charge/Ft	Oz	0.161
ROOM TEMPERATURE			Design Pressure	PSIG	550 / 340
Indoor (Cooling/Heating)	°F	62~90 / 32~86	Connection Wiring	16AWG*4, Stranded, Unshielded	
Outdoor (Cooling/Heating)	°F	5~122 / 5~86	Power Supply	Ph/V/Hz	1 / 208/230 / 60
SPECIFICATIONS			RECOMMENDED ACCESSORIES		
Refrigerant Type	R410A		BZ33-WCON1 .3496301		
Thermostat Type	Wireless Remote		Description	Wired Controller	
Warranty	Yes*		Compatible with	All Breeze33 Indoor Mini Split Equipment	

\*5 year warranty on parts. 7 year warranty on compressor.