

**COMFORT SERIES****24,000 BTU****BZ33-HP24WALL2-C****BZ33-HP24OUT2-C****FEATURES**

- Two-way draining
- Golden Fin anti-corrosive coating
- Auto restart function
- Crank case & base pan heater included
- Auto defrost
- 24-hour timer
- Wireless remote control included
- 208/230V, single phase

**TWO-WAY DRAINING**

Piping, drainage, and connections are able to be installed on the right and left sides.

**FOLLOW ME MODE**

Senses indoor temperature at handheld remote or Breeze33 wired controller, rather than at the indoor equipment.

**GOLDEN FIN COATING**

Prevents corrosive build-up and improves efficiency while protecting the condenser from harsh weather and elements.

**AUTO DEFROST**

In low temperatures, the auto defrost feature will keep the evaporator from freezing.

**AUTO RESTART**

In the event of a power failure, the unit will remember and restart the previous settings when power returns.

**24-HOUR TIMER**

Preset the unit to automatically turn on or off.

UNIT			COMFORT SERIES		
ID NO.	MODEL		INDOOR FAN MOTOR		
Indoor	.3473406	BZ33-HP24WALL2-C	Input	W	58
Outdoor	.3473407	BZ33-HP24OUT2-C	Output	W	64
COOLING			RLA	A	0.206
Capacity (Range)	BTU/H	24,000 (6,850 - 24,500)	Speed (High/Med/Low)	r/min	1,100 / 900 / 750
Input	W	2,500	Air Flow (High/Med/Low)	CFM	706 / 588 / 450
Rated Current	A	11.0	Noise Level (High/Med/Low)	dBA	48 / 42.5 / 34
EER	BTU/W	9.5	INDOOR UNIT DIMENSIONS		
SEER	BTU/W	17	Product (W x D x H)	In	42-1/2 x 8-9/10 x 13-1/5
HEATING			Packaging (W x D x H)	In	45-1/2 x 16-3/10 x 12-2/5
Capacity (Range)	BTU/H	24,000 (7,200 - 25,000)	Net/Gross Weight	Lbs	30.2 / 39.68
Input	W	2,200	OUTDOOR FAN MOTOR		
Rated Current	A	9.6	Input	W	50
COP	W/W	3.2	Output	W	115
HSPF4	BTU/W	9.5	RLA	A	0.5
HSPF5	BTU/W	8.0	Speed	r/min	800 / 750 / 650
COMPRESSOR			Air Flow	CFM	1,823
Type	Rotary		Noise Level	dBA	58
Capacity	W	7,715	OUTDOOR UNIT DIMENSIONS		
Input	W	2,085	Product (W x D x H)	In	33-1/5 x 14-3/10 x 27-3/5
Rated Current (RLA)	A	9.45	Packaging (W x D x H)	In	38 x 15-1/2 x 30-1/10
Refrigerant Oil/Charge	mL	Ester Oil VG74 / 670	Net/Gross Weight	Lbs	105.16 / 112.22
REFRIGERANT PIPING			ELECTRICAL DATA		
Liquid	In	3/8	Min. Circuit Ampacity	A	20
Gas	In	5/8	Max. Fuse	A	25
Max. Refrigerant Pipe Length	Ft	98	Refrigerant Precharge	Ft	25
Max. Different in Level	Ft	66	Additional Charge/Ft	Oz	0.322
ROOM TEMPERATURE			Design Pressure	PSIG	550 / 340
Indoor (Cooling/Heating)	°F	62~90 / 32~86	Connection Wiring	16AWG*4, Stranded, Unshielded	
Outdoor (Cooling/Heating)	°F	5~122 / 5~86	Power Supply	Ph/V/Hz	1 / 208/230 / 60
SPECIFICATIONS			RECOMMENDED ACCESSORIES		
Refrigerant Type	R410A		BZ33-WCON1 .3496301		
Thermostat Type	Wireless Remote		Description	Wired Controller	
Warranty	Yes*		Compatible with	All Breeze33 Indoor Mini Split Equipment	

\*5 year warranty on parts. 7 year warranty on compressor.