

**COMFORT SERIES****36,000 BTU****BZ33-HP36WALL2-2****BZ33-HP36OUT2-C****FEATURES**

- Two-way draining
- Golden Fin anti-corrosive coating
- Auto restart function
- Crank case & base pan heater included
- Auto defrost
- 24-hour timer
- Wireless remote control included
- 208/230V, single phase

**TWO-WAY DRAINING**

Piping, drainage, and connections are able to be installed on the right and left sides.

**FOLLOW ME MODE**

Senses indoor temperature at handheld remote or Breeze33 wired controller, rather than at the indoor equipment.

**GOLDEN FIN COATING**

Prevents corrosive build-up and improves efficiency while protecting the condenser from harsh weather and elements.

**AUTO DEFROST**

In low temperatures, the auto defrost feature will keep the evaporator from freezing.

**AUTO RESTART**

In the event of a power failure, the unit will remember and restart the previous settings when power returns.

**24-HOUR TIMER**

Preset the unit to automatically turn on or off.

COMFORT SERIES		
UNIT	ID NO.	MODEL
Indoor	.3478328	BZ33-HP36WALL2-2
Outdoor	.3473409	BZ33-HP36OUT2-C
COOLING		
Capacity (Range)	BTU/H	36,000 (10,100 - 36,520)
Input	W	4,185
Rated Current	A	18.5
EER	BTU/W	8.6
SEER	BTU/W	16
HEATING		
Capacity (Range)	BTU/H	36,000 (10,400 - 37,560)
Input	W	4,135
Rated Current	A	18.3
COP	W/W	2.55
HSPF4	BTU/W	8.5
HSPF5	BTU/W	7
COMPRESSOR		
Type		Rotary
Capacity	W	25,760
Input	W	2,070
Rated Current (RLA)	A	17
Refrigerant Oil/Charge	mL	Ester Oil VG74 / 670
REFRIGERANT PIPING		
Liquid	In	3/8
Gas	In	5/8
Max. Refrigerant Pipe Length	Ft	213
Max. Different in Level	Ft	98
ROOM TEMPERATURE		
Indoor (Cooling/Heating)	°F	62~90 / 32~86
Outdoor (Cooling/Heating)	°F	32~122 / 5~86
SPECIFICATIONS		
Refrigerant Type		R410A
Thermostat Type		Wireless Remote
Warranty		Yes*
INDOOR FAN MOTOR		
Input	W	72
Output	W	60
RLA	A	0.23
Speed (High/Med/Low)	r/min	1,200 / 1,100 / 900
Air Flow (High/Med/Low)	CFM	677 / 589 / 471
Noise Level (High/Med/Low)	dBA	48.5 / 44 / 38
INDOOR UNIT DIMENSIONS		
Product (W x D x H)	In	46-7/10 x 10-1/10 x 13-2/5
Packaging (W x D x H)	In	49-4/5 x 13-2/5 x 16-1/2
Net/Gross Weight	Lbs	40.12 / 50.26
OUTDOOR FAN MOTOR		
Input	W	150
Output	W	120
RLA	A	0.6
Speed	r/min	810 / 700 / 500
Air Flow	CFM	2,943
Noise Level	dBA	63
OUTDOOR UNIT DIMENSIONS		
Product (W x D x H)	In	37-1/4 x 16-1/10 x 31-9/10
Packaging (W x D x H)	In	42-9/10 x 19-7/10 x 34-1/2
Net/Gross Weight	Lbs	143.3 / 153.22
ELECTRICAL DATA		
Min. Circuit Ampacity	A	25
Max. Fuse	A	35
Refrigerant Precharge	Ft	25
Additional Charge/Ft	Oz	0.322
Design Pressure	PSIG	550 / 340
Connection Wiring		16AWG*4, Stranded, Unshielded
Power Supply	Ph/V/Hz	1 / 208/230 / 60
RECOMMENDED ACCESSORIES		
BZ33-WCON1		.3496301
Description		Wired Controller
Compatible with		All Breeze33 Indoor Mini Split Equipment

