

**COMFORT SERIES****36,000 BTU****BZ33-HP36WALL2-C****BZ33-HP36OUT2-C****FEATURES**

- Two-way draining
- Golden Fin anti-corrosive coating
- Auto restart function
- Crank case & base pan heater included
- Auto defrost
- 24-hour timer
- Wireless remote control included
- 208/230V, single phase

**TWO-WAY DRAINING**

Piping, drainage, and connections are able to be installed on the right and left sides.

**FOLLOW ME MODE**

Senses indoor temperature at handheld remote or Breeze33 wired controller, rather than at the indoor equipment.

**GOLDEN FIN COATING**

Prevents corrosive build-up and improves efficiency while protecting the condenser from harsh weather and elements.

**AUTO DEFROST**

In low temperatures, the auto defrost feature will keep the evaporator from freezing.

**AUTO RESTART**

In the event of a power failure, the unit will remember and restart the previous settings when power returns.

**24-HOUR TIMER**

Preset the unit to automatically turn on or off.

UNIT			COMFORT SERIES		
ID NO.	MODEL		INDOOR FAN MOTOR		
Indoor	.3473408	BZ33-HP36WALL2-C	Input	W	58
Outdoor	.3473409	BZ33-HP36OUT2-C	Output	W	64
			RLA	A	0.206
			Speed (High/Med/Low)	r/min	1,200 / 1,050 / 750
			Air Flow (High/Med/Low)	CFM	853 / 647 / 471
			Noise Level (High/Med/Low)	dBA	52 / 44 / 36
COOLING			INDOOR UNIT DIMENSIONS		
Capacity (Range)	BTU/H	36,000 (10,100 - 36,500)	Product (W x D x H)	In	49-3/5 x 11-1/10 x 14-1/4
Input	W	4,235	Packaging (W x D x H)	In	52-7/10 x 17-7/10 x 15
Rated Current	A	18.5	Net/Gross Weight	Lbs	43.2 / 55.6
EER	BTU/W	8.5	OUTDOOR FAN MOTOR		
SEER	BTU/W	16	Input	W	150
			Output	W	120
			RLA	A	0.6
			Speed	r/min	810 / 700 / 500
			Air Flow	CFM	2,943
			Noise Level	dBA	63
HEATING			OUTDOOR UNIT DIMENSIONS		
Capacity (Range)	BTU/H	36,000 (10,400 - 37,500)	Product (W x D x H)	In	37-1/4 x 16-1/10 x 31-9/10
Input	W	3,835	Packaging (W x D x H)	In	42-9/10 x 19-7/10 x 34-1/2
Rated Current	A	16.7	Net/Gross Weight	Lbs	143.3 / 153.22
COP	W/W	2.75	ELECTRICAL DATA		
HSPF4	BTU/W	10	Min. Circuit Ampacity	A	25
HSPF5	BTU/W	8.4	Max. Fuse	A	35
			Refrigerant Precharge	Ft	25
			Additional Charge/Ft	Oz	0.322
			Design Pressure	PSIG	550 / 340
			Connection Wiring		16AWG*4, Stranded, Unshielded
			Power Supply	Ph/V/Hz	1 / 208/230 / 60
COMPRESSOR			RECOMMENDED ACCESSORIES		
Type		Rotary	<b>BZ33-WCON1</b>	<b>.3496301</b>	
Capacity	W	25,760	Description		Wired Controller
Input	W	2,070	Compatible with		All Breeze33 Indoor Mini Split Equipment
Rated Current (RLA)	A	17			
Refrigerant Oil/Charge	mL	Ester Oil VG74 / 670			
REFRIGERANT PIPING					
Liquid	In	3/8			
Gas	In	5/8			
Max. Refrigerant Pipe Length	Ft	213			
Max. Different in Level	Ft	98			
ROOM TEMPERATURE					
Indoor (Cooling/Heating)	°F	62~90 / 32~86			
Outdoor (Cooling/Heating)	°F	32~122 / 5~86			
SPECIFICATIONS					
Refrigerant Type		R410A			
Thermostat Type		Wireless Remote			
Warranty		Yes*			

\*5 year warranty on parts. 7 year warranty on compressor.