

PREMIER SERIES**9,000 BTU****BZ33-HYP09WALL2-P****BZ33-HYP09HPOUT2-P****FEATURES**

- Two-way draining
- Heating operation down to -22F
- Low Ambient cooling down to -22F
- Golden Fin anti-corrosive coating
- Auto restart function
- Crank case & base pan heater included
- Auto defrost
- 24-hour timer
- Wireless remote control included
- 208/230V, single phase

TWO-WAY DRAINING

Piping, drainage, and connections are able to be installed on the right and left sides.

FOLLOW ME MODE

Senses indoor temperature at handheld remote or Breeze33 wired controller, rather than at the indoor equipment.

GOLDEN FIN COATING

Prevents corrosive build-up and improves efficiency while protecting the condenser from harsh weather and elements.

AUTO DEFROST

In low temperatures, the auto defrost feature will keep the evaporator from freezing.

AUTO RESTART

In the event of a power failure, the unit will remember and restart the previous settings when power returns.

24-HOUR TIMER

Preset the unit to automatically turn on or off.



INDOOR/OUTDOOR HYPER PRO MINI-SPLIT SYSTEM

UNIT			INDOOR FAN MOTOR			PREMIER SERIES		
Indoor	.3473419	BZ33-HYP09WALL2-P	Input	W	50			
Outdoor	.3473411	BZ33-HYP09HPOUT2-P	Output	W	20			
			RLA	A	0.06			
			Speed (High/Med/Low)	r/min	1,170 / 900 / 700			
			Air Flow (High/Med/Low)	CFM	418 / 324 / 247			
			Noise Level (High/Med/Low)	dBA	42 / 33 / 24.5			
COOLING			INDOOR UNIT DIMENSIONS					
Capacity (Range)	BTU/H	9,000 (3,100 - 12,000)	Product (W x D x H)	In	32-9/10 x 7-4/5 x 11			
Input	W	620	Packaging (W x D x H)	In	35-4/5 x 10-3/5 x 14			
Rated Current	A	2.7	Net/Gross Weight	Lbs	19.84 / 25.35			
EER	BTU/W	14.5						
SEER	BTU/W	25						
HEATING			OUTDOOR FAN MOTOR					
Capacity (Range)	BTU/H	10,000 (3,000 - 12,500)	Input	W	58			
Input	W	835	Output	W	34			
Rated Current	A	3.6	RLA	A	0.39			
COP	W/W	3.83	Speed	r/min	810 / 700 / 450			
HSPF4	BTU/W	11.2	Air Flow	CFM	1,120			
HSPF5	BTU/W	9	Noise Level	dBA	55.5			
COMPRESSOR			OUTDOOR UNIT DIMENSIONS					
Type		Rotary	Product (W x D x H)	In	31-1/2 x 13-1/10 x 21-4/5			
Capacity	W	11,594	Packaging (W x D x H)	In	36-1/5 x 15-3/10 x 24-1/5			
Input	W	858	Net/Gross Weight	Lbs	88.2 / 93.7			
Rated Current (RLA)	A	5.25						
Refrigerant Oil/Charge	mL	Ester Oil VG74 / 500						
REFRIGERANT PIPING			ELECTRICAL DATA					
Liquid	In	1/4	Min. Circuit Ampacity	A	9			
Gas	In	3/8	Max. Fuse	A	15			
Max. Refrigerant Pipe Length	Ft	82	Refrigerant Precharge	Ft	25			
Max. Different in Level	Ft	33	Additional Charge/Ft	Oz	0.161			
ROOM TEMPERATURE			Design Pressure	PSIG	550 / 340			
Indoor (Cooling/Heating)	°F	62~90 / 32~86	Connection Wiring		16AWG*4, Stranded, Unshielded			
Outdoor (Cooling/Heating)	°F	-22~122 / -22~86	Power Supply	Ph/V/Hz	1 / 208/230 / 60			
SPECIFICATIONS			RECOMMENDED ACCESSORIES					
Refrigerant Type		R410A	BZ33-WCON1		.3496301			
Thermostat Type		Wireless Remote	Description		Wired Controller			
Warranty		Yes*	Compatible with		All Breeze33 Indoor Mini Split Equipment			

*5 year warranty on parts. 7 year warranty on compressor.

