HYPER PRO MINI-SPLIT SYSTEM

18,000 BTU

PREMIER SERIES

BZ33-HYP18WALL2-P



BZ33-HYP18HPOUT2-P



FEATURES

- Two-way draining
- Heating operation down to -22F
- Low Ambient cooling down to -22F
- Golden Fin anti-corrosive coating
- Auto restart function
- Crank case & base pan heater included
- Auto defrost
- 24-hour timer
- Wireless remote control included
- 208/230V, single phase

TWO-WAY DRAINING

Piping, drainage, and connections are able to be installed on the right and left sides.

FOLLOW ME MODE

Senses indoor temperature at handheld remote or Breeze33 wired controller, rather than at the indoor equipment.

GOLDEN FIN COATING

Prevents corrosive build-up and improves efficiency while protecting the condenser from harsh weather and elements.

AUTO DEFROST

In low temperatures, the auto defrost feature will keep the evaporator from freezing.

AUTO RESTART

In the event of a power failure, the unit will remember and restart the previous settings when power returns.

24-HOUR TIMER

Preset the unit to automatically turn on or off.



INDOOR/OUTDOOR

HYPER PRO MINI-SPLIT SYSTEM

UNIT	ID NO.	MODEL	INDOOR FAN MOTOR		PREMIER SERIES
Indoor	.3473423	BZ33-HYP18WALL2-P	Input	W	58
Outdoor	.3473413	BZ33-HYP18HPOUT2-P	Output	W	64
			RLA	Α	0.206
COOLING			Speed (High/Med/Low)	r/min	1,100 / 900 / 700
Capacity (Range)	BTU/H	17,000 (6,100 - 18,500)	Air Flow (High/Med/Low)	CFM	599 / 411 / 353
Input	W	1,360	Noise Level (High/Med/Low)	dBA	45.5 / 36 / 26.5
Rated Current	Α	5.95			
EER	BTU/W	12.5	INDOOR UNIT DIMENSIONS		
SEER	BTU/W	20	Product (W x D x H)	In	39 x 8-3/5 x 12-2/5
			Packaging (W x D x H)	In	42 x 11-4/5 x 15-3/4
HEATING			Net/Gross Weight	Lbs	26.98 / 34.83
Capacity (Range)	BTU/H	18,000 (6,300 - 19,500)			
Input	W	1,685	OUTDOOR FAN MOTOR		
Rated Current	Α	7.4	Input	W	50
COP	W/W	3.13	Output	W	115
HSPF4	BTU/W	10.3	RLA	Α	0.5
HSPF5	BTU/W	8.8	Speed	r/min	850 / 700 / 450
			Air Flow	CFM	1,355
COMPRESSOR			Noise Level	dBA	57.5
Туре		Rotary			
Capacity	W	24,345	OUTDOOR UNIT DIMENSIONS		
Input	W	1,970	Product (W x D x H)	ln	33-1/4 x 14-3/10 x 27-3/5
Rated Current (RLA)	Α	12.3	Packaging (W x D x H)	In	38 x 15-1/2 x 29-7/10
Refrigerant Oil/Charge	mL	Ester Oil VG74 / 670	Net/Gross Weight	Lbs	107.4 / 115.1
REFRIGERANT PIPING			ELECTRICAL DATA		
Liquid	In	1/4	Min. Circuit Ampacity	А	18
Gas	In	1/2	Max. Fuse	Α	25
Max. Refrigerant Pipe Length	Ft	98	Refrigerant Precharge	Ft	25
Max. Different in Level	Ft	66	Additional Charge/Ft	Oz	0.161
			Design Pressure	PSIG	550 / 340
ROOM TEMPERATURE			Connection Wiring		16AWG*4, Stranded, Unshielded
Indoor (Cooling/Heating)	°F	62~90 / 32~86	Power Supply	Ph/V/Hz	1 / 208/230 / 60
Outdoor (Cooling/Heating)	°F	-22~122 / -22~86			
			RECOMMENDED ACCESSORIES		
SPECIFICATIONS					
Refrigerant Type		R410A	BZ33-WCON1		.3496301
Thermostat Type		Wireless Remote	Description		Wired Controller
Warranty		Yes*	Compatible with	All Bree	eze33 Indoor Mini Split Equipment





^{*5} year warranty on parts. 7 year warranty on compressor.