

# MAF8-4", MAF11-5"




## FEATURES

- Pleats reinforced with continuous metal grid and integrated cardboard fingers
- Recommended max. operating temperature: 140°F
- Recommended to be replaced after 12 months of use
- ETL classified per UL Standard 900 for flammability

## SPECIFICATIONS

Model	ID No.	Nominal Size (in.) (H x W x D)	Actual Size (in.) (H x W x D)	Rated Air Flow (CFM)	Initial Resistance (W.C.)	MERV	Media Area (sq. ft.)	PI/Ft.
<b>MAF8-4"</b>								
BZ33MAF16204	.3540700	16 x 20 x 4	15-3/8 x 19-3/8 x 3-5/8	1111	0.17	8	11.7	9
BZ33MAF16254	.3540701	16 x 25 x 4	15-3/8 x 24-3/8 x 3-5/8	1389	0.17	8	14.8	9
BZ33MAF20204	.3540702	20 x 20 x 4	19-3/8 x 19-3/8 x 3-5/8	1389	0.17	8	14.7	9
BZ33MAF20254	.3540704	20 x 25 x 4	19-3/8 x 24-3/8 x 3-5/8	1736	0.17	8	18.5	9
<b>MAF11-5"</b>								
BZ33MAF16255	.3551230	16 x 25 x 5	15-3/4 x 24-3/4 x 4-3/8	1370	0.19	11	21.1	10
BZ33MAF20205	.3551231	20 x 20 x 5	19-5/8 x 19-7/8 x 4-3/8	1370	0.19	11	21.7	10
BZ33MAF20255	.3551232	20 x 25 x 5	19-7/8 x 24-3/4 x 4-3/8	1710	0.19	11	27.1	10



## BREEZE33 AIR FILTER REPLACEMENT CHART

Breeze33	Lennox	Honeywell	Carrier	Bryant	Purolator	Koch	Trion	AAF Flanders
<b>MAF8-4"</b>								
BZ33MAF16204 BZ33MAF16254 BZ33MAF20204 BZ33MAF20254	—	—	—	—	HE40 PAF11	XL8 XL10 XL11	—	Natural Aire
<b>MAF11-5"</b>								
BZ33MAF16255	X6670	FC35A1001 FC100A1029 FC200E1029	EXPXXFIL0016 EXPXXUNV0016 EXPXXLMC0016 FILCCAR0016	FILXXCAR0116 P102-1625	—	—	255649-105	—
BZ33MAF20205	X0585	203721 FC35A1019 FC100A1011 FC200E1011	—	FILXXFNC0021	—	—	255649-103	—
BZ33MAF20255	X6673	FC35A1027 FC100A1037 FC200E1037	EXPXXFIL0020 EXPXXUNV0020 EXPXXLMC0200 FILCCAR002	FILXXCAR0020 P102-2025	—	—	255649-102 229990-002 229990-102	—