

# **PREMIER SERIES**

#### BZ33-MSAHU24-P



#### **FLEXIBLE HEATING**

The unit can be used with Premier Series Hyper Pro outdoor equipment. It can also be paired with Breeze33 electric heat strips.

#### **UNIVERSAL IDU**

The unit is compatible with Breeze33 multi zone systems. This allows independent IDU control and keeps every room comfortable.

## FEATURES

- Premier Series
- Auto restart function
- Golden Fin anti-corrosive coating
- Self-diagnosis and auto-protection
- Refrigerant leakage detect
- Error alarm
- Compatible with 36K & 48K Multi Zone
  Outdoor Units
- Compatible with 24K Hyper Pro Premier Series Outdoor Units
- Compatible with any 24v HVAC thermostat

#### **MULTI-POSITION**

Full multi-position installation makes the unit capable of upflow, horizontal left or horizontal right configurations.

## INDOOR **AIR HANDLER**

#### 24,000 BTU



### INDOOR AIR HANDLER

### **PREMIER SERIES**

UNIT	ID NO.	MODEL
Indoor	.3510122	BZ33-MSAHU24-P
COOLING		
Capacity (Range)	BTU/H	20,800 (7,500 - 26,000)
EER	BTU/W	12.5
SEER	BTU/W	20
HEATING Capacity (Range)	BTU/H	29,000 (5,600 - 35,000)
COP	W	3.48
HSPF4	BTU/W	10
HSPF5	BTU/W	7.5
COMPRESSOR		
Туре		Rotary
Capacity	W	7,135
Input	W	1,970
Refrigerant Oil/Charge	mL	VG74 / 670
<b>REFRIGERANT PIPING</b>		
Liquid	In	3/8
Gas	In	5/8
Max. Length	Ft	164
Max. Height Difference	Ft	82

Refrigerant Type		R410A
Warranty		Yes*
FAN MOTOR		
Input	W	150
Speed	r/min	<1,000
Air Flow	CFM	2,235.3
Noise Level	dBA	60
UNIT DIMENSIONS		
Product (W x D x H)	In	21 x 19-3/5 x 48-4/5
Packaging (W x D x H)	In	24-3/5 x 22-2/5 x 51-1/5
Net/Gross Weight	Lbs	141 / 156
ELECTRICAL DATA		
	A	20
	A	20 30
Min. Circuit Ampacity Max. Fuse		
Min. Circuit Ampacity Max. Fuse Refrigerant Precharge	A	30
Min. Circuit Ampacity Max. Fuse Refrigerant Precharge	A Ft	30 20
Min. Circuit Ampacity Max. Fuse Refrigerant Precharge Additional Charge/Ft	A Ft Oz	30 20 0.21
Min. Circuit Ampacity Max. Fuse Refrigerant Precharge Additional Charge/Ft Design Pressure Power Supply	A Ft Oz PSIG	30 20 0.21 550 / 340
Min. Circuit Ampacity Max. Fuse Refrigerant Precharge Additional Charge/Ft Design Pressure Power Supply	A Ft Oz PSIG	30 20 0.21 550 / 340 1 / 208/230 / 60
Min. Circuit Ampacity Max. Fuse Refrigerant Precharge Additional Charge/Ft Design Pressure Power Supply RECOMMENDED ACCESSORIES	A Ft Oz PSIG Ph/V/Hz	30 20 0.21 550 / 340 1 / 208/230 / 60 .351134
Min. Circuit Ampacity Max. Fuse Refrigerant Precharge Additional Charge/Ft Design Pressure Power Supply RECOMMENDED ACCESSORIES BZ33-EHS05-P	A Ft Oz PSIG Ph/V/Hz	30 20 0.21 550 / 340

\*5 year warranty on parts. 7 year warranty on compressor.

Description

Compatible with



10kW Electric Heat Strips, 208-230V

BZ33-MSAHU24-P Air Handler